CS-800

MOTION CONTROLS-



Standard Features:

- ◆ Runs up to eight hoists
- ◆ 50 amp Hubbell input connector
- Hubbell power and control output connectors
- ◆ 50 amp main emergency disconnect connector standard
- ◆ Safety keyswitch for on/off and phase reversal
- Input phase reversal
- Phase power indicators
- Remote hand held pendant with LED indicators and 25 foot cord



The CS-800 is the most economical member of our modular line of controllers. Ready to run eight individual hoists, both power distribution and relay control for the hoists reside in the same compact unit. Manual control is provided through a remote pendant with a 25 foot cable. The remote has up/down select switches and LED indicators for each hoist, momentary run button, and an emergency stop switch that controls a disconnect contactor. Not only is the CS-800 a stand-alone unit, it can also be used with our line of controls. Add four CS-800's to the TR-3200 Manual Control and run 32 hoists manually or plug four CS-800's into our Computerized Hoist Control to run 32 hoists under computer control.

Pendant / Remote Features:

- ◆ Hand-held control pendant with 25' cable
- ♦ 8 way up/down select switches & indicators
- Momentary run switch
- · Emergency stop switch

Optional Features:

- Rack mountable version at no extra cost
- Road Case
- Phase rotation indicator
- Remote with fully detachable cord

Dimensions without case:

Standard: 16.5 in. W x 21 in. H x 6 in. D Rack Mount: 19 in. W x 21 in. H x 6 in. D

Electrical:

208-240 vac, 50 amps, 50-60 hz, 3 phase (Single phase and other voltages available.)

Ventura, CA (805) 650-0877 FAX (805) 650-0360 http://www.skjonberg.com